

THERM DYNAMICS

FLAMELESS. EFFICIENT. HEATERS.

TD 1200

PERFORMANCE

- FUEL: **Diesel #2**
- MAX BTU OUTPUT: **1,200,000**
- Efficiency: **90%+**
- CFM: **7,500+**
- STATIC PRESSURE: **3.25" lbs**
- TEMPERATURE: **180°F**
- MAX FUEL CONSUMPTION: **9.3 GPH**

POWER PLANT

- **JOHN DEERE 6068**
- **CAT C6.6**

DIMENSIONS

- Weight, Empty: **Approx. 4,300 lbs**
- Weight, Full: **Approx. 5,770 lbs**
- Cabinet Height: **7'0"**
- Cabinet Width: **5'8"**
- Cabinet Length: **11'6"**
- Overall Length: **14'0"**

FUEL CAPACITY

- **210 GALS**

No flame. No fumes. No fuss.

Ideal for applications where an open flameless spark-risk is out of the question; the **TD1200** excels at providing **1,200,000 BTUs** of clean, dry heat.

The patented technology uses diesel power to agitate hydraulic oil in a flameless, sparkless, low-pressure environment. The oil is cooled and circulated, not burned, providing a clean pollution free discharge to the target environment. Safety features are incorporated to protect the investment of your Therm Dynamics heaters.

All heaters are equipped with a set of four shut-off switches that terminate the engine when excessive pressures, speed or water temperatures are detected. This unit meets or exceeds OSHA, MSHA, and API standards for use in most areas.

CERTIFIED TO CSA B 140.8.1967 & UL733-1993
REPORT NUMBER: 489-D-01-2

*Clean.
Safe
Heat!*



1.855.350.HEAT (4328)

9502 87th Ave Morinville, Alberta | www.artictherm.com



ARTIC THERM
International Ltd.

A Division of Enterprise Group Inc.