

# THERM DYNAMICS

FLAMELESS. EFFICIENT. HEATERS.

## TD 400

### PERFORMANCE

- FUEL: **Diesel #2**
- MAX BTU OUTPUT: **400,000**
- CFM: **4,000+**
- STATIC PRESSURE: **3.00" lbs**
- TEMPERATURE: **140°F**
- MAX FUEL CONSUMPTION: **3.3 GPH**

### POWER PLANT

- **KUBOTA V2403 59HP**

### DIMENSIONS

- Weight, Empty: **Approx. 2,820 lbs**
- Weight, Full: **Approx. 3,520 lbs**
- Cabinet Height: **6'0"**
- Cabinet Width: **3'0"**
- Cabinet Length: **9'6"**
- Overall Length: **12'4"**
- Overall Width: **5'6"**
- Overall Height: **6'6"**

### FUEL CAPACITY

- **100 GALS** • **200 GALS OPTIONAL**
- **150 GALS DOUBLE CONTAINMENT**

## No flame. No fumes. No fuss.

Ideal for applications where an open flameless spark-risk is out of the question; the **TD400** excels at providing **400,000 BTUs** of clean, dry heat.

The patented technology uses diesel power to agitate hydraulic oil in a flameless, sparkless, low-pressure environment. The oil is cooled and circulated, not burned, providing a clean pollution free discharge to the target environment. Safety features are incorporated to protect the investment of your Therm Dynamics heaters.

All heaters are equipped with a set of four shut-off switches that terminate the engine when excessive pressures, speed or water temperatures are detected. This unit meets or exceeds OSHA, MSHA, and API standards for use in most areas.

**CERTIFIED TO CSA B 140.8.1967 & UL733-1993**

**REPORT NUMBER: 489-D-01-2**



*Clean.  
Safe  
Heat!*

1.855.350.HEAT (4328)

9502 87<sup>th</sup> Ave Morinville, Alberta | [www.artictherm.com](http://www.artictherm.com)



**ARTIC THERM**  
International Ltd.

A Division of Enterprise Group Inc.