

# THERM DYNAMICS

FLAMELESS. EFFICIENT. HEATERS.

## PERFORMANCE

- FUEL: **Diesel #2**
- MAX BTU OUTPUT: **750,000**
- Efficiency: **90%+**
- CFM: **7,500+**
- STATIC PRESSURE: **3.25"**
- TEMPERATURE: **180°F**
- MAX FUEL CONSUMPTION: **5.9GPH**

## POWER PLANT

- JOHN DEERE 6068
- CAT C6.6

## DIMENSIONS

- Weight, Empty: **Approx. 3,980 lbs**
- Weight, Full: **Approx. 5,450 lbs**
- Cabinet Length: **11'6"**
- Overall Length: **14'0"**
- Overall Width: **5'6"**
- Overall Height: **7'0"**

## FUEL CAPACITY

- **210 GALS**

*Clean,  
Safe  
Heat!*

## No flame. No fumes. No fuss.

# TD 750

Ideal for applications where an open flame or spark-risk is out of the question; the **TD750** excels at providing **750,000 BTUs** of clean, dry heat.

The patented technology uses diesel power engine to agitate hydraulic oil in flameless, sparkless, low-pressure environment. In addition, an overspeed air intake shut-off valve is standard equipment. The oil is heated and circulated, not burned, providing a clean pollution free discharge to the target environment. Safety features are incorporated to protect the investment of your Therm Dynamics heater.

All heaters are equipped with a set of four shut-off switches that terminate the engine when excessive pressures, speed or water temperatures are detected.

## CERTIFIED TO

UL733-2013 & CSA B 140.8.1967(R2015) STANDARDS  
REPORT NUMBER: #0489HH001S



**THERM DYNAMICS**  
FLAMELESS. EFFICIENT. HEATERS.

Therm Dynamics Mfg. Inc. 27077 S Gayle Ave, Tea, SD 57064 Office: 605-498-1050

Visit us at [www.thermdynamics.com](http://www.thermdynamics.com) or email [info@thermdynamics.com](mailto:info@thermdynamics.com) for further information.

©2016 by Therm Dynamics Mfg. Inc. All rights reserved. US Patent #5,819,724, #6,186,138B1, and #9,366,170B2