X ATI 625 - Specifications



Temperature	82°C / 180°F
BTU's	625,000
CFM	4,500+
Fuel Consumption P/Hr	4.9 lmp Gal / 18.5 L
Fuel Capacity	200 Imp Gal / 757 L
Weight (empty)	3,300 Lbs
Weight (full)	4,420 Lbs
Height	6'6"
Width	5'6"
Length	12'4"

BENEFITS

- Self Contained and Portable
- Thermostat Control
- EUB Approved / Working up to 7 Meters from the Wellhead
- Proven Results with Alberta Research Council
- Breathable Heat
- Allows Work to Occur Simultaneously
- Increased Engine Longevity
- Intrinsically Safe
- Reduce Costs from Reduced Timelines
- Double Containment Available

APPLICATIONS

- Construction Sites
- Vessel / Tank Coat Curing
- Equipment & Ground Thawing
- Emergency & Facility Heating
- Well Head & B.O.P. Heating
- Temporary Structures / Healthcare
- Plant Turnarounds/Start Ups
- De Humidifying / Drying
- Flood Clean Up
- Concrete Curing

PIONEERS IN FLAMELESS HEATING TECHNOLOGY

Rated 90%+ Efficient

* Efficiency rating is based off of ideal heating conditions and has a tolerance of +/- 3%

HEAD OFFICE 9502-87th Ave Morinville, Alberta T8R 1K6 (780) 939.3141 info@artictherm.com

Drayton Valley Whitecourt Grande Prairie Fort St. John

Toll Free: 1-855-350-HEAT (4328)



artictherm.com